



Note:

These are the DEVELOPED shapes of the saloon roof and doghouse roof – that is the shape to set out on a flat sheet of ply so that it is the correct shape when curved and laid on the boat.

Make saloon roof from single sheet 1220 wide. Make doghouse roof from two sheets of ply with a butt join on Frame -2800

DO NOT make either roof with join down centreline. They will not lay fair.

Dimensions given are 9mm greater each side than inside of coamings, to allow for 9mm ply coaming. In practice, cut ply a little bigger (say an extra 5mm each side) to allow for fitting and cleaning off.

Although the coachroof front, doghouse front and Frame -3700 are flat, perpendicular and square across the boat, the roof centrelines slope down fwd. Thus on the developed shape the fwd and aft ends are not square across but lose length on the aft edges and gain length on the fwd edges.

In practice, allow about 20mm on the fwd ends to allow for fitting and then clean off flush with the saloon and doghouse fronts.

Also check from boat after Coamings are fitted to ensure dimensions are sufficient.

See Instructions for further detail.

Length along centreline is 1201mm

 Whisstock boats and boat plans	support@whisstock.com	
	Design 165	Scale 1/10
	Developed shapes of Saloon & Doghouse Roofs	Date Jul 30 2014
	© Debenriver Ltd 2014 All Rights Reserved	Plan No. 165/003/010 Issue No. 01
		All dimensions in millimetres unless otherwise noted